

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 905 746 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
31.03.1999 Bulletin 1999/13

(51) Int Cl.⁶: H01L 21/00

(21) Application number: 98870056.3

(22) Date of filing: 20.03.1998

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Mertens, Paul
3150 Haacht (BE)
• Meuris, Mark
3140 Keerbergen (BE)
• Heyns, Marc
3210 Linden (BE)

(30) Priority: 24.09.1997 US 59929

(71) Applicant: INTERUNIVERSITAIR
MICRO-ELEKTRONICA CENTRUM VZW
3001 Heverlee (BE)


(74) Representative: Van Malderen, Joelle et al
Office Van Malderen,
Place Reine Fabiola 6/1
1083 Bruxelles (BE)

(54) Method of removing a liquid from a surface of a rotating substrate

(57) A method of removing a liquid, i.e. a wet processing liquid, from a surface of at least one substrate is disclosed. A liquid is supplied on a surface of substrate. Simultaneously or thereafter besides the liquid also a gaseous substance can be supplied thereby creating at least locally a sharply defined liquid-vapour boundary. The gaseous substance and the liquid can be

selected such that the gaseous substance is miscible with the liquid and when mixed with the liquid yields a mixture having a surface tension lower than that of the liquid. According to the invention, the substrate is subjected to a rotary movement at a speed to guide said liquid-vapour boundary over said substrate thereby removing said liquid from said substrate.

Figure 1





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

H01L 21/00

A1

(11) International Publication Number:

WO 99/16109

(43) International Publication Date:

1 April 1999 (01.04.99)

(21) International Application Number: PCT/BE98/00140

(22) International Filing Date: 24 September 1998 (24.09.98)

(30) Priority Data:

60/059,929	24 September 1997 (24.09.97)	US
98870056.3	20 March 1998 (20.03.98)	EP
60/079,688	27 March 1998 (27.03.98)	US
60/098,038	27 August 1998 (27.08.98)	US

(71) Applicant (for all designated States except US): INTERUNIVERSITAIR MICRO-ELEKTRONICA CENTRUM VERENIGING ZONDER WINSTBEJAG [BE/BE]; Kapeldreef 75, B-3001 Heverlee (BE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MERTENS, Paul [BE/BE]; Beverdijk 34, B-3150 Haacht (BE). MEURIS, Marc [BE/BE]; Dornien Liekenslaan 27, B-3140 Keerbergen (BE). HEYNS, Marc [BE/BE]; Merelnest 14, B-3210 Linden (BE).


(74) Agents: VAN MALDEREN, Joëlle et al.; Office Van Malderen, Place Reine Fabiola 6/1, B-1083 Brussels (BE).

(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: METHOD AND APPARATUS FOR REMOVING A LIQUID FROM A SURFACE



(57) Abstract

A method and an apparatus for removing a liquid, i.e. a wet processing liquid, from at least one surface of at least one substrate is disclosed. A liquid is supplied on a surface of substrate. Simultaneously or thereafter the liquid or the substrate is locally heated to thereby reduce the surface tension of said liquid. By doing so, at least locally a sharply-defined-liquid-ambient boundary is created. According to the invention, the substrate is subjected to a rotary movement at a speed to guide said liquid-ambient boundary over the surface of the substrate thereby removing said liquid from said surface.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 December 2002 (19.12.2002)

PCT

(10) International Publication Number
WO 02/101795 A2

(51) International Patent Classification: H01L 21/00

(21) International Application Number: PCT/US02/18761

(22) International Filing Date: 12 June 2002 (12.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/297,736 12 June 2001 (12.06.2001) US
60/304,920 11 July 2001 (11.07.2001) US
60/316,725 30 August 2001 (30.08.2001) US

(71) Applicants: VERTEQ, INC [US/US]; 1241 E. Dyer Road, Suite 100, Santa Ana, CA 92705-6533 (US).
INTERUNIVERSITAIR MICROELEKTRONICA CENTRUM (IMEC)* [BE/BE]; Kapeldreef 75, B-B-3001 Leuven (BE).

(72) Inventors: LAUERHAAS, Jeffrey, M.; Slachthuislaan 1 bus 212, B-3000 Leuven (BE). NICOLOSI JR., Thomas, J.; 22976 Luciana, Mission Viejo, CA 92691 (US). MERTENS, Paul; Dijkstra 30 A, B-B-2820 Bonheiden (BE). FYEN, William; Geldenaalsebaan 159, B-B-3001 Heverlee (BE).

(74) Agent: ARAI, Katsuhiko; KNOBBE, MARTENS, OLSON & BEAR, LLP, 620 Newport Center Drive, 16th Floor, Newport Beach, CA 92660 (US).


(81) Designated States (*national*): CA, IL, JP, KR, NO, SG.

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: MEGASONIC CLEANER AND DRYER SYSTEM



(57) Abstract: An apparatus for drying a generally flat substrate (114) that has been cleaned has a rotatable support (110) for supporting the substrate (114), a substrate drying assembly (120), and a controller (147). The substrate drying assembly (120) includes a substrate drying assembly support arm (130), an outlet for applying liquid to an upper surface of the substrate (114), and an outlet for applying a drying vapor to the upper surface of the substrate (114). The substrate drying assembly (120) is configured to position the liquid applying outlet and to position the vapor applying outlet above a portion of the substrate (114). The controller (147) causes the substrate drying assembly (120) to be retracted over the upper surface of the substrate (114) at a faster rate near a center of the substrate (114) than near a periphery of the substrate (114).

WO 02/101795 A2